



# DECX High Capacity Precision Balance

## External Calibration

Download  
Catalogue



- A High quality load cell
- Quick stabilization
- Full range tare
- LCD Display
- Overload protection
- Unit: g, ct, oz, lb, GN, %, pcs

**DECX** High Capacity Precision Balance



### External Calibration

External Linear Calibration



### High Precision Load Cell

High measuring range up to 30kg is provided with high capacity load cell,



### Software for data collection

Optional software for communication with the scale provides the ability to collect data, control the measurement process ...

**30kg/0,1g**

**External  
Calibration**

**Big Pan Size**

**310\*220mm**

**High Capacity  
Load Cell**

**Piece Counting**

Type	DECX6	DECX10	DECX15	DECX20	DECX30
Maximum Capacity (kg)	6	10	15	20	30
Accuracy Class	III				
Division (g)	0,1g				
Stabilization time	≤2sec				
Operating temperature	15°C~30°C, fluctuation range <5°C/h				
Operating Relative humidity (RH)	40%~80%				
Power supply	AC110-240V 50/60Hz DC5V-2A (adaptor)				
Pan Size (mm)	255*190mm				
Calibration	External				
Display	LCD with backlight				
Interface	RS232C				
System	Check Weighing, Parts Counting, Percentage Weighing				
Optional Accessories	Rechargeable battery, Under Hook, Double Display, Printer, Instruction Manual,				
Dimension(L*W*H)	32×26×11 (L*W*H)				
Gross weight	4				

Please note

If this Balance does not match the specific needs of your application, or some options are not listed for sale, please feel free to contact us. Our manufacturing engineers will come up with technical solutions to meet your needs. We reserve the right to change technical specifications at any time.

## COLO LabExperts

Laboratory Equipment production and Distribution

[www.colo.si](http://www.colo.si)

Presernov Trg 9

8000 Novo Mesto

Slovenia

tel. +386 590 48 880 E-mail: [office@colo.si](mailto:office@colo.si)

[www.colo.si](http://www.colo.si)

© 2021 COLO Distributors Price List V1