Colo Science
Laboratory & Scientific Equipment

COLO.SCIENCE · TECHNICAL SPECIFICATION

ODRA2 Thermostatic Water Bath

RT+5 to 100 °C · 2 holes in one row · 6.1 L stainless steel tank 300 × 135 × 150 mm · PID controller

ODRA2 is a compact thermostatic water bath with two holes in one row, for two beakers or flasks side by side. The 6.1 L stainless steel tank is heated by a U-shaped heater directly in the water, and a PID controller with set and actual value display keeps the temperature from RT+5 °C to 100 °C. Each hole has concentric rings for vessels of different sizes.

RT+5 TO 100 °C | 0.1 °C RESOLUTION | 2 HOLES | 6.1 L TANK | U-SHAPED HEATER | PID CONTROL | LID WITH RINGS | 500 W

Document type: **Technical Specification Sheet**
Product: **ODRA2 thermostatic water bath**
Order code (SKU): **PRO2965**
Format: **A4 landscape · CORE-TECHSPEC 1.2**

ODRA2 PRODUCT PAGE | HEATING & THERMAL PROCESSING | HEATING CATALOGUE | REQUEST QUOTE

Order code

TWO HOLES
ODRA2 · PRO2965
RT+5 to 100 °C · 6.1 L



ODRA2 · 6.1 L stainless steel tank, lid with two holes and rings

VOLUME
6.1 L

ADDRESS / HQ
Polje ob Sotli 4
SI-3255, Slovenia

CONTACT
sales@colo.si
+386 70 713 437

Technical data sheet · Informational document · Controlled electronic document
Contact: sales@colo.si · +386 70 713 437

ODRA2 · technical specification

RT+5 to 100 °C · 2 holes in one row · 6.1 L stainless steel tank 300 × 135 × 150 mm · PID controller

RT+5–100 °C | 6.1 L | 2 HOLES | PID | STAINLESS STEEL — Compact two-hole water bath

Product Overview

Application profile

Two vessels: two beakers, flasks or bottles at the same temperature.

Parallel samples: a sample and a control, or two reagents, side by side.

Warming and thawing: reagents, media and samples before use.

Teaching and QC: simple constant-temperature steps on a small bench footprint.

Key features

Tank: 6.1 L stainless steel tank, 300 × 135 × 150 mm, deep-drawn with rounded corners.

Heating: U-shaped stainless steel heater directly in the water, 500 W.

Control: PID controller with two displays (actual PV and set SV value), auto-tuning and alarm indication.

Temperature: RT+5 °C to 100 °C, resolution 0.1 °C.

Lid: stainless steel lid with two holes, each with concentric rings — the openings adapt to the vessel size.

Tray: perforated stainless steel tray on the tank bottom, over the heater.

Housing: powder-coated steel, power and output switches on the front panel.

Core technical summary

Parameter	Specification
Model	ODRA2
Temperature range	RT+5 to 100 °C
Resolution	0.1 °C
Holes	2, in one row
Tank volume	6.1 L
Tank W × D × H	300 × 135 × 150 mm
Control	PID, PV / SV display
Supply	220 V, 50 Hz, 500 W



Tank with U-shaped heater, lid with two holes and perforated tray

TEMPERATURE	RESOLUTION	TANK	POWER
RT+5 to 100 °C	0.1 °C	6.1 L	500 W

RT = room temperature. Values measured with water, without load. Suitability for a specific method is confirmed in the COLO.Science quotation.

ODRA2 PRODUCT PAGE | HEATING & THERMAL PROCESSING | HEATING CATALOGUE | REQUEST QUOTE

Model data · ODRA2

Parameter	ODRA2
Order code (SKU)	PRO2965
Holes	2, in one row
Tank volume	6.1 L
Tank size W × D × H	300 × 135 × 150 mm
Packing W × D × H	400 × 250 × 250 mm
Weight (packed)	7 kg


Technical Specifications

Temperature and control	Value
Temperature range	RT+5 to 100 °C
Resolution	0.1 °C
Stability	±0.5 °C
Control	PID, auto-tuning
Display	LED, actual (PV) and set (SV) value
Indicators	run, output, auto-tune, alarm

Construction and supply	Value
Tank	deep-drawn stainless steel, rounded corners
Heater	U-shaped stainless steel tube, in water
Lid	stainless steel, 2 holes with concentric rings
Tray	perforated stainless steel
Housing	steel, powder coated
Supply	220 V, 50 Hz, 500 W



6.1 L stainless steel tank with perforated tray



U-shaped stainless steel heater directly in the water

Values measured with water, without load, at room temperature. Dimensions W × D × H. Fill the tank above the heater before switching on the heating.

ODRA2 PRODUCT PAGE | HEATING & THERMAL PROCESSING | HEATING CATALOGUE | REQUEST QUOTE

Ordering, Configuration Guidance and Support



ODRA2 · compact two-hole water bath

Ordering information

Item	SKU
ODRA2 · thermostatic water bath, 2 holes, 6.1 L	PRO2965
Standard: lid with two holes and concentric rings, perforated tray	included
Baths with 1, 4 or 6 holes	on request

Configuration checklist

Vessels: beakers or flasks per run (up to two) → ring size.

Temperature: working temperature and time per run.

Water: distilled or deionised water; level above the heater.

Room: small bench space, earthed 220 V socket.

SUPPLIER AND SUPPORT

COLO Lab Experts

Polje ob Sotli 4, SI-3255, Slovenia

Selection guidance: Send what you heat, the vessels per run and the temperature. COLO.Science will confirm the configuration and the delivery time.

QUICK CONTACT

colo.si

sales@colo.si

+386 70 713 437

Ask us:
Price and current discount, delivery time, installation and service — write to sales@colo.si or call us.

ODRA2 PRODUCT PAGE | HEATING & THERMAL PROCESSING | HEATING CATALOGUE | REQUEST QUOTE