

PRO6152 • HF-Resistant pH Composite Electrode

Glass body • long-life reference • ceramic junction • refillable • S7

PH 0–14 0–80 °C REFILLABLE CERAMIC JUNCTION $\Phi 12 \times 120$ MM S7 – BNC (Q9)



PRO6152 is a glass pH electrode for acidic wastewater that contains fluorine, resistant to hydrofluoric acid up to 2000 ppm HF. Glass body, ceramic junction and a refillable long-life reference.

How it is built



PH SENSOR

Spherical bulb

General-purpose glass membrane for common solutions.



BODY

Glass

Lead-free glass, easy to clean, suitable for organic solutions. Breakable.



JUNCTION

Ceramic

Good permeability, stable potential.



CONNECTOR

S7 – BNC (Q9)

S7 head on the electrode; S7-BNC cable to the meter.

RANGE

pH 0 – 14

TEMPERATURE

0 – 80 °C

MAINTENANCE

Refillable, 3 M KCl

BEST FOR

Fluorine-containing wastewater

Why choose it

Stable for longer: the long-life reference keeps a steady potential over a longer service time and a wider temperature range than a plain Ag/AgCl reference.

Refillable: the reference electrolyte is topped up with 3 M KCl filling solution.

Ceramic junction: good permeability, stable potential.

PRO6152 • HF-Resistant pH Composite Electrode

Technical parameters

Parameter	Specification
Model / order code	PRO6152
Electrode type	pH composite (combination) electrode
Measuring range	pH 0 – 14
Working temperature	0 – 80 °C
pH sensor	Hemispherical glass bulb
Body material	Glass
Reference system	Long-life reference
Junction	Ceramic
Fill solution	3 M KCl
Temperature sensor	None
Dimensions	Φ12 × 120 mm
Connector	S7 – BNC (Q9)
HF resistance	≤ 2000 ppm HF

Temperature compensation: the electrode has no built-in temperature sensor; use the meter's separate temperature probe or manual compensation.



BNC (Q9) on the meter side. The electrode has an S7 head; the S7-BNC cable connects it to pH meters with a BNC input.

Recommended samples

Field	Sample types • recommended
Environmental	Highly concentrated acidic wastewater containing fluorine (≤ 2000 ppm HF)

Ordering data

Order code: PRO6152

Connector: S7 – BNC (Q9) — check the meter input before ordering.

Accessories: S7-BNC (Q9) cable, 3 M KCl filling solution.

Choose another electrode when

Above 80 °C: use the high-temperature electrode (to 120 °C).

Everyday aqueous samples: a general-purpose electrode is sufficient.

SUPPLIER AND SUPPORT

COLO Lab Experts
Polje ob Sotli 4, SI-3255, Slovenia

QUICK CONTACT



COLO.SCIENCE • ELECTRODE SELECTION SUPPORT

Not sure this is the right electrode for your sample?

Send us the meter model, sample type, pH range and temperature — we will confirm the electrode or propose a better match from the catalogue.

Technical values are given for product selection. The configuration confirmed in the COLO.Science quotation is binding for delivery.

[PRO6152 PRODUCT PAGE](#)
[ELECTROCHEMISTRY — OVERVIEW](#)
[ELECTRODE CATALOGUE](#)
[REQUEST QUOTE](#)