

PRO6160 • Conductivity Electrode $k = 10$ with ATC

Cell constant $k = 10 \cdot 2000 - 200\,000 \mu\text{S}/\text{cm}$ • built-in temperature sensor • 5-pin aviation

K = 10 2000 - 200 000 MS/CM ATC 0-80 °C $\Phi 12 \times 120$ MM 5-PIN AVIATION



PRO6160 is a glass conductivity cell with constant $k = 10$ and a built-in temperature sensor for high-conductivity samples — concentrated wastewater and seawater up to 200 mS/cm.

How it is built



CELL CONSTANT
 $k = 10 \text{ cm}^{-1}$
For high-conductivity samples.



CELL MATERIAL
Glass
Lead-free glass, easy to clean, suitable for organic solutions. Breakable.



TEMPERATURE SENSOR
Built-in (ATC)
Measures temperature and conductivity at the same time.



CONNECTOR
5-pin aviation
Fits conductivity meters with a 5-pin aviation input.

CELL CONSTANT
 $k = 10 \text{ cm}^{-1}$

RANGE
2000 - 200 000 $\mu\text{S}/\text{cm}$

TEMPERATURE
ATC, 0 - 80 °C

BEST FOR
High-conductivity samples

Why choose it

Matched to the range: cell constant $k = 10$ covers 2000 - 200 000 $\mu\text{S}/\text{cm}$.

Temperature compensated: conductivity and temperature are measured at the same point, at the same time.

PRO6160 • Conductivity Electrode $k = 10$ with ATC

Technical parameters

Parameter	Specification
Model / order code	PRO6160
Electrode type	Conductivity electrode
Cell constant	$k = 10 \text{ cm}^{-1}$
Conductivity range	2000 – 200 000 $\mu\text{S/cm}$
Temperature measurement	0 – 80 °C (ATC)
Working temperature	0 – 80 °C
Sensor material	Glass
Flow cell	None
Dimensions	$\Phi 12 \times 120 \text{ mm}$
Connector	5-pin aviation

Calibration: calibrate with a conductivity standard close to the expected sample value.



5-pin aviation connector. Plugs into conductivity meters with a 5-pin aviation input.

Recommended samples

Sample	Conductivity
Municipal wastewater, wastewater, seawater, juice	20 $\mu\text{S/cm}$ – 200 mS/cm

How to choose the cell constant

Sample	Range	Cell
Ultrapure water	0.055 – 2 $\mu\text{S/cm}$	$k = 0.01$
Pure, ion-exchange water	1 – 200 $\mu\text{S/cm}$	$k = 0.1$
Drinking, surface, rain water	2 – 3000 $\mu\text{S/cm}$	$k = 1$
Wastewater, seawater, juice	20 $\mu\text{S/cm}$ – 200 mS/cm	$k = 1 / k = 10$

Ordering data

Order code: PRO6160

Connector: 5-pin aviation — check the meter input before ordering.

Accessories: conductivity standard solutions.

SUPPLIER AND SUPPORT

COLO Lab Experts
Polje ob Sotli 4, SI-3255, Slovenia

QUICK CONTACT



COLO.SCIENCE • ELECTRODE SELECTION SUPPORT

Not sure which cell constant your samples need?

Send us the meter model, sample type and expected conductivity — we will confirm the electrode or propose a better match from the catalogue.

Technical values are given for product selection. The configuration confirmed in the COLO.Science quotation is binding for delivery.

PRO6160 PRODUCT PAGE

ELECTROCHEMISTRY — OVERVIEW

ELECTRODE CATALOGUE

REQUEST QUOTE